

PMT SERVICE DECLARATION

CARPORT

Unique identification code of the product type	PMT CARPORT
Project No.	See shipping note
Purpose of use	Car park roofing with optional installation of a PV system
Manufacturer	Premium Mounting Technologies GmbH & Co. KG Industriestraße 25 D-95346 Stadtsteinach
System(s) for the assessment and verification of constancy of performance	2+
Harmonized standard	EN 1090-1:2009 + A1:2011
Notified body	NB 2451

KEY CHARACTERISTIC

Tolerances for dimensions and format
Welding suitability
Fracture strength
Impact strength
Load capacity
Deformation in the serviceability limit state
Fatigue strength
Fire resistance
Fire behaviour
Release of cadmium and its compounds
Release of radioactive radiation
Durability

DECLARED PERFORMANCE

EN 1090-2, DIN EN 13920 A for length measurements, C for angular measurements, F for straightness, Levelness and parallelism
NPD (EN 5817)
Min. 27J at 20°C, Yield strength min. 235N/mm ²
Min. 27J bei 20°C, Yield strength min. 235N/mm ²
Dimensioning according to EN 1999-1-1
See static dimensioning
NPD
See static dimensioning
Steel A1
NPD
NPD
Hot dip galvanised according to DIN EN ISO 1461

The performance of the above product is in conformity with the declared performance. The manufacturer referred to above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) No 305/2011. Signed for and on behalf of the manufacturer by:

Name

City

Date

Signature

Jörg Weber

Stadtsteinach

18.05.2022

